



5DO69750
Island flue
Stainless steel and black glass

Output, consumption

- Voltage: 220 – 240 V
- Total connected load: 228.4 W
- Energy efficiency class: A*
- Average power consumption: 49.6 kWh/year
- Fan efficiency class: A*
- Light efficiency class: A*
- Grease filter efficiency class: C*
- Noise min./max. Normal level: 48/58 dB*
- Fan output max. Normal level/Intensive level*: • in extraction mode 550 m³/h / 700 m³/h • in circulation mode 420 m³/h / 560 m³/h * According to EU Regulation No. 65/2014 / Fan capacity according to EN 61591

Equipment / comfort

- Stainless steel and black glass
- For ceiling installation above kitchen islands
- Optional extraction or circulation mode (carbon filter required for circulation mode)
- Electronic control
- 4-level fan power (3 power levels + 1 intensive level) controllable through I-Drive and Touch Control with LED display
- Intensive levels with automatic reset
- Automatic three-level power overrun of 5/10 and 20 minutes
- Metal grease filter saturation indicator
- Activatable carbon filter saturation indicator
- Powerful and quiet blower
- Uniform, bright lighting with 4 x 2.1 W LED lamps
- Illuminance: 239.4 lux
- Colour temperature: 4.000 K
- Metal grease filter, dishwasher-safe
- Including exhaust air shaft

Optional accessories:

- 5Z 9101X1: Carbon filter

Technical data and dimensions

- Appliance dimensions, extraction: 660 – 1080 x 900 x 600 mm
- Appliance dimensions, circulation: 730 – 1150 x 900 x 600 mm
- Length of connection cable (cm): 150

Optional accessories:

- 5Z 9101X1: Carbon filter

Available color options:

Accessories:

Features:

- Device type: island fair
- Color of the fireplace: stainless steel
- Design: Wandesse
- Approval certificates: CE
- Length of connection cable (cm): 150
- Height of the fireplate: min. 660 max. 1150
- Height of the unit without chimney (mm): 83
- Net weight (kg): 25
- Control: I-Drive and Touch Control with LED display
- Regulation of power levels: 3 + intensive
- Max. Fan power exhaust air operation (m³ / h): 550
- Blower power for intensive stage exhaust air operation (m³ / h): 700
- Max. Fan speed recirculation mode (m³ / h): 420
- Blower power at intensive stage circulating air operation (m³ / h): 560
- Number of lamps (pieces): 4
- Sound power (dB (A) re 1 pW): min. 48 | Max. 58
- Diameter of exhaust air outlet (mm): 150
- Material of grease filter: aluminum
- Odor filter: no | As an accessory
- Type of air duct: Optional exhaust air or recirculated air
- Type of lamps: LED
- Total power of the lamps (W): 4x2,1 W
- Type of grease filter: aluminum
- Filter change reminder: Yes

Consumption and connection values:

- Connected load (W): 224.2
- Voltage (V): 220/240
- Frequency (Hz): 50/60
- Plug type: Schuko
- Length of connection cable (cm): 150
- Type of installation: Inselesse
- Net weight (kg): 25
- Position of the fan: motor in the housing

EAN-Nr.:4251003101072

