



<p><b>5DO99750</b>  <b>Wall flue</b>  <b>Stainless steel and black glass screen</b></p> <p><b>Output, consumption</b></p> <ul style="list-style-type: none"> <li>• Voltage: 220 – 240 V</li> <li>• Total connected load: 224.2 kW</li> <li>• Energy efficiency class: A*</li> <li>• Average power consumption: 50 kWh/year*</li> <li>• Fan efficiency class: A*</li> <li>• Light efficiency class: A*</li> <li>• Grease filter efficiency class: C*</li> <li>• Noise min./max. Normal level: 48/58 dB*</li> <li>• Fan output max. Normal level/ Intensive level*:                      in extraction mode 550 m<sup>3</sup>/h / 700 m<sup>3</sup>/h                      in circulation mode 420 m<sup>3</sup>/h / 560 m<sup>3</sup>/h                      * According to EU Regulation No. 65/2014/ Fan capacity according to EN 61591</li> </ul> <p><b>Equipment / comfort</b></p> <ul style="list-style-type: none"> <li>• Stainless steel and black glass screen</li> <li>• For wall installation above hobs</li> <li>• Optional extraction or circulation mode (carbon filter required for circulation mode)</li> <li>• Electronic control</li> <li>• 4-level fan power (3 power levels + 1 intensive level) controllable through I-Drive and Touch Control with LED display</li> <li>• Intensive levels with automatic reset</li> <li>• Automatic three-level blower overrun of 5/10 and 20 minutes</li> <li>• Metal grease filter saturation indicator</li> <li>• Activatable carbon filter saturation indicator</li> <li>• Powerful and quiet blower</li> <li>• Uniform, bright lighting with 2 x 2.1 W LED lamps</li> <li>• Illuminance: 119.7 lux</li> <li>• Colour temperature: 4.000 K</li> <li>• Metal grease filter, dishwasher-safe</li> <li>• Including exhaust air shaft</li> </ul> <p><b>Optional accessories:</b></p> <ul style="list-style-type: none"> <li>• 5Z9102X1: Carbon filter</li> </ul> <p><b>Technical data and dimensions</b></p> <ul style="list-style-type: none"> <li>• Appliance dimensions, extraction: 660 – 1080 x 900 x 490 mm</li> <li>• Appliance dimensions, circulation: 730 – 1150 x 900 x 490 mm</li> <li>• Length of connection cable (cm): 150</li> </ul>
---

<p><b>Optional accessories:</b></p> <ul style="list-style-type: none"> <li>• 5Z9102X1: Carbon filter</li> </ul>
<p><b>Available color options:</b></p>
<p><b>Accessories:</b></p>

<p><b>Features:</b></p> <ul style="list-style-type: none"> <li>• Device type: Wandesse</li> <li>• Color of the fireplace: stainless steel</li> <li>• Design: Wandesse</li> <li>• Approval certificates: CE</li> <li>• Length of connection cable (cm): 150</li> <li>• Height of the fireplace: min. 660 max. 1150</li> <li>• Height of the unit without chimney (mm): 83</li> <li>• Net weight (kg): 20</li> <li>• Control: I-Drive and TouchControl with LED display</li> <li>• Regulation of power levels: 3 + intensive</li> <li>• Max. Fan power exhaust air operation (m<sup>3</sup> / h): 550</li> <li>• Blower power for intensive stage exhaust air operation (m<sup>3</sup> / h): 700</li> <li>• Max. Fan speed recirculation mode (m<sup>3</sup> / h): 420</li> <li>• Blower power at intensive stage circulating air operation (m<sup>3</sup> / h): 560</li> <li>• Number of lamps (pieces): 2</li> <li>• Sound power (dB (A) re 1 pW): min. 48   Max. 58</li> <li>• Diameter of exhaust air outlet (mm): 150</li> <li>• Material of grease filter: aluminum</li> <li>• Odor filter: no   As an accessory</li> <li>• Type of air duct: Optional exhaust air or recirculated air</li> <li>• Type of lamps: LED</li> <li>• Total power of the lamps (W): 2x2,1 W</li> <li>• Type of grease filter: aluminum</li> <li>• Filter change reminder: Yes</li> </ul>
<p><b>Consumption and connection values:</b></p> <ul style="list-style-type: none"> <li>• Connected load (W): 224.2</li> <li>• Voltage (V): 220/240</li> <li>• Frequency (Hz): 50/60</li> <li>• Plug type: Schuko</li> <li>• Type of installation: Wandesse</li> <li>• Net weight (kg): 20</li> <li>• Dimensions of the appliance, with chimney (if fitted) (in): / x x</li> <li>• Length of connection cable (cm): 150</li> </ul>

EAN-Nr.: 4251003101089

