



5DS69760
stainless steel with black glass
Cooker Hood 90 cm

Power / Consumption

- Voltage: 220 - 240 V
- Total connected load: 274 W
- Energy efficiency class: A++
- Average energy consumption: 43 kWh / year*
- Fan efficiency class: A*
- Lighting efficiency class: A*
- Grease filter efficiency class: B*
- Noise min./max. normal level: 66 / 69 dB*
- Fan power max. normal stage / intensive stage*:
with exhaust air operation max. 580 m³ / h / 700 m³ / h
with circulating air operation max. 450 m³ / h / intensive 500 m³ / h
* According to EU regulation no. 65/2014 / fan capacity according to EN 61591

Equipment / Comfort

- stainless steel and black glass screen
- For wall mounting above hotplates
- smart slider
- touch control
- Optional exhaust air or recirculation operation
(a starter set is required for recirculation operation)
- Electronic control
- Fan power 4-stage (3 power stages + 1 intensive stage)
adjustable via Smart Slider with LED display
- Intensive stages with automatic reset
- Powerful and quiet blower
- Uniform, bright illumination with 2 x 2 W LED lamps
- Illuminance: 180 lux
- Colour temperature: 4.000 K
- Metal grease filter, dishwasher safe
- Incl. exhaust air shaft

Technical data and dimensions

- Unit dimensions exhaust air: 79.0 - 106.0 x 90.0 x 46.0 cm
- Unit dimensions circulating air: 79.0 - 106.0 x 90.0 x 46.0 cm

Accessories:

Special accessories:

- SZ 9114X1: Activated carbon filter
- SZ 9114X2: Longlife activated carbon filter
- SZ 9119X1: Shaft extension upper chimney
stainless steel 990 mm

Available colour variations:



Features:

- Device type: T-Shape hood
- Colour of the fireplace: stainless steel
- Type: Wall
- Approval certificates: CE
- Length of connecting cable (cm): 150
- Height of the fireplace (mm): 540+470
- Height of the unit without chimney (mm): 60
- Control: Touch controls with slider
- Control of power levels: 3+int
- Max. Fan power - exhaust air operation (m³/h): 580
- Blower output for intensive stage exhaust operation (m³/h): 700
- Number of lamps (pcs): 2
- Sound power (dB(A) re 1 pW): Max 66, Int. 69
- Diameter of exhaust port (mm): 150
- Grease filter material: Aluminum
- Odour filter: Optional
- Type of air ducting: upwards
- Delay Shut off modes: yes
- Type of lamps: LED
- Total wattage of lamps (W): 2x2W
- Filter change reminder: yes

Consumption and connection values:

- Connected load (W): 274
- Fuse protection (A): -
- Voltage (V): 220-240
- Frequency (Hz): 50-60
- Connector type: EU
- Type of installation: Wall
- Housing material: stainless steel
- Approval certificates: CE
- Connector type: EU
- Required distance between hob / stove: 650mm
- Position of fan: Motor in chimney
- Max. Fan power in recirculation mode (CFM): -
- Flow direction: upwards
- Backwater flap: yes, diameter 150 mm
- Length of connecting cable: 150 cm

EAN: 4251003104073

