



5IX60260
Glass ceramic black
Downdraft 60cm

Power / Consumption
 • Voltage: 220 - 240 V
 • Total connected load 7.4 kW
 • Cooking zones:
 2 x Ø 160 mm, 1.4 kW (max. power stage 2.0 kW)
 2 x 190x210 mm (combined induction)
 1 x 2.1 kW (max. power stage 3.0 kW)
 1 x 1.6 kW (max. power stage 1.85 kW)

Equipment / Comfort
 • 4 HighSpeed cooking zones
 • TouchControl
 • Timer
 • 10 performance levels
 • Digital display of the cooking steps (LED)
 • Main switch with stop function
 • 3x power stage
 • Parental control
 • Residual heat display per cooking zone
 • Pot detection
 • countdown
 • 1 x combined induction
 • Frameless

Technical data and dimensions (HxWxD)
 • Device dimensions: 59 x 600 x 520 mm
 • Installation dimensions: 0-59 x 561 x 484 mm
 • Device dimensions (packed): 1040 x 740 x 505 mm
 • Net weight (kg): 21.2
 • Gross weight (kg): 32

Accessories

Available colour variations:

Special accessories:

- 5Z6005KF1 - Charcoal filter
- 5Z9104X1 - Air outlet kit right
- SLG51X90 - Plinth ventilation grille

Equipment features:

- Device type: Induction with integrated extractor fan
- Design: Installation
- Energy source: electric
- Position of the control unit: Front
- Flush mountable
- Approval certificates: CE
- Connection cable length (cm): 1500

Consumption and connection values:

Electrical connection value (W): 7400
 Protection (A): -
 Voltage (V): 220-240
 Frequency (Hz): 50; 60
 Connector type: without connector
 Minimum distance from counter front (mm): 50
 Minimum distance from rear wall (mm): 42

EAN-Nr. 4251003105087

