



EAN-Nr.: 4251003106862

5IX60290 Stand-alone induction hob with build in fan

Power / Consumption

- Voltage: 220 - 240 V
- Total connected load: 7,4 kW
- 4 Induction cooking zone with Booster:
- 2 cooking zones Ø 17,5 cm with 1,4 kW (2,1 kW)
- 2 cooking zones Ø 16,0 cm with 1,4 kW (1,85 kW)
- Energy efficiency class: B
- Grease filter efficiency class: B

Equipment / Comfort

- Frameless
- Boost function for all induction cooking zones
- Startup-Boost
- Smart Slider
- Touch Control
- 11 power levels
- Simultaneous timers for each zone
- Egg timer
- Child lock
- Break
- Recall
- Keep warm function (~70°C)
- Demo-Mode
- Digital display (red)
- Residual heat indication for each cooking zone
- Überlauferkennung
- Overflow detection
- Quick Start-Function
- Pot detection
- Automatic switching on of the ventilation system when a cooking zone is used

Planning information

- Suitable for exhaust and recirculation installation
- The first relevant 90° bend is included with the fan
- Compatible with flat duct system Naber Compar Flow 150 or comparable systems
- Min. cabinet width 600 mm
- Worktop depth min. 600 mm (if niche panelling is planned, correspondingly deeper)
- niche panelling correspondingly deeper)
- Plinth height min. 100 mm (depending on the duct system used)

Dimensions

- Appliances dimensions: (H/W/D) 201 x 590 x 520 mm
- Installation dimensions (H/W/D) 197 x 560 x 500 mm

Accessories

Available colour variations:

Special accessories:

- 5Z9402X1 - Charcoal filter
- 5Z9404X1 - Grease filter with Meshtissue (Grease filter efficiency class A)

Features

- Device type: induction hob
- Energy source: electric
- Number of cooking zones that can be used simultaneously: 4
- Cooking zones with Booster: 4
- Wide of the appliances (mm): 590
- Net weight (kg): 22,7
- Gross weight (kg): 24,2
- Residual heat display: Yes
- Position of the control system: Front
- Touch control / Slider
- LED Display
- Colour: black
- Approbationscertifikate: CE / UKCA
- Cooking zones with Booster: 4
- Grease filter efficiency class: B

LüfterleistungAbluftleistung:

- 9 power levels + 1 Intensive level
- Automatic fan run-on
- Saturation indicator for grease and charcoal filters
- Exhaust cap.: max. 424 m³/h, int. 441 m³/h
- Recirculation cap.: max. 339 m³/h, int. 353 m³/h
- Noise values
- Normal level: min. 34 dB(A) max. 69 dB(A) Intensive level: 72 dB(A)
- Energy efficiency class: B

Consumption and connection values:

- Total connected load (W): 7400
- Voltage (V): 220-240
- Frequenz (Hz): 50; 60
- Colour: black
- Energy source: electric
- Approbationscertifikate: CE / UKCA
- Plug: -
- Number of cooking zones that can be used simultaneously: 4
- Appliances dimensions: (mm): 201 x 590 x 520
- Installation dimensions (mm): 197 x 560 x 500
- Packed dimensions (cm): 100 x 76 x 27
- Net weight: 22,7 kg
- Gross weight: 24,2 kg