



5IX92291
Glass ceramic black
Downdraft 90cm

Power / Consumption
 • Voltage: 220 - 240 V
 • Total connected load 7.4 kW
 • Cooking zones:
 4 x 190 x 210 mm, 2.1 kW (max. power stage 3 kW)

Equipment / Comfort
 • 4 HighSpeed cooking zones
 • TouchControl
 • Timer
 • 10 power levels - 2x combined induction
 • Digital display of the cooking steps (LED)
 • Main switch with stop function
 • Power stage for all induction cooking zones
 • Parental control
 • Residual heat display per cooking zone
 • Pot detection
 • countdown
 • Frameless

Technical data and dimensions (HxWxD)
 • Unit dimensions: (h/w/d) 0-5 x 900 x 530 mm
 • Installation dimensions: (h/w/d) 50-55 x 860 x 490 mm
 • Device dimensions (packed): 1040 x 740 x 505
 • Net weight (kg): 24,71
 • Gross weight (kg): 36,2

Accessories



Equipment features:
 • Device type: Induction with integrated extractor fan
 • Design: Installation
 • Energy source: electric
 • Position of the control unit: Front
 • Flush mountable
 • Approval certificates: CE
 • Length of connection cable (cm): 150

Available colour variations:

Consumption and connection values:
 • Electrical connection value (W): 7400
 • Protection (A): -
 • Voltage (V): 220-240
 • Frequency (Hz): 50; 60
 • Connector type: without connector
 • Minimum distance from counter front (in): 50
 • Minimum distance from rear wall (in): 42

Special accessories:
 2x Set Charcoal Filter 5Z9009LF1
 Air outlet kit right 5Z9104X1
 Plinth ventilation grille SLG5IX90

EAN-Nr.: 4251003105063

