



5IX94291
Glass ceramic black
Downdraft 90cm

Power / Consumption

- Voltage: 220 - 240 V
- Total connected load 7.4 kW
- Cooking zones:
 - 4 x 190x210 mm, 2.1 kW (max. power stage 3 kW)
 - 2 x combined induction 3,7 kW

Equipment / Comfort

- 4 HighSpeed cooking zones
- TouchControl with timer
- 10 performance levels
- Digital display of the cooking steps
- Main switch with stop function
- Power stage for all induction cooking zones
- Parental control
- Residual heat display per cooking zone
- Pot detection
- countdown
- Operating instructions
- Frameless

Technical data and dimensions (HxWxD)

- Device dimensions: (h/w/d) 58 x 900 x 530 mm
- Installation dimensions: (h/w/d) 58 x 862 x 495 mm
- Device dimensions (packed): 1040 x 740 x 505
- Net weight (kg): 30,8
- Gross weight (kg): 39,65

Accessories

Equipment features:

- Type of appliance: Cooking unit glass ceramic
- Design: Built-in device
- Energy source: electric
- Position of the control unit: Front
- Approval certificates: CE
- Length of connection cable (cm): 150

Available colour variations:

Consumption and connection values:

- Electrical connection value (W): 7400
- Protection (A): -
- Voltage (V): 220-240
- Frequency (Hz): 50; 60
- Connector type: without connector
- Minimum distance from counter front (in): 50
- Minimum distance from rear wall (in): 42

Special accessories:

- 5Z915X1 Charcoal filter
- 5Z9104X1 Air outlet kit right
- SLG5IX90 Plinth ventilation grille

EAN-Nr. 4251003105070

