



**5IX99291**  
**Glass ceramic black**  
**Downdraft 90cm**

**Power / Consumption**

- Energy efficiency class: A+++
- Average energy consumption: 30.8 kW/a
- Fan efficiency class: A
- Lighting efficiency class: -
- Grease filter efficiency class: B
- Total connected load: 165 W
- voltage: 220/240V
- Sound power (dB(A) re 1 pW): min 45 | max 65 Int. 70

**Equipment / Comfort**

- Suitable for mounting in kitchen line or island
- Choice of exhaust air or recirculation mode - Electronic opening of the extractor hood
- Fan capacity 6-stage adjustable by TouchControl
- 7-segment LED display
- For exhaust air 5 power levels + 1 intensive level
- With recirculated air 6 power levels
- 2 intensive levels with automatic reset
- Automatic, three-stage fan run from 5/10 and 20 minutes with LED display
- Filter change reminder: Yes
- Metal grease and carbon filter saturation indicator (LED)
- Cleaning/emptying of metal grease filter: automatically after 40 operating hours
- Automatic overrun with recirculated air
- Water collector: 0.75 litre capacity
- Powerful and quiet blower
- Metal grease filter, dishwasher safe
- Performance according to EN 61591:
  - Blower capacity - exhaust air operation (m<sup>3</sup>/h): 576
  - Fan power intensive air extraction mode (m<sup>3</sup>/h) : 734
  - Blower capacity-circulating air operation (m<sup>3</sup>/h): 450
  - Blower capacity in intensive air recirculation mode (m<sup>3</sup>/h): 560

**Technical data and dimensions (HxWxD)**

- Device dimensions: 58 x 900 x 530 mm radius 5
- Installation dimensions: 58 x 862 x 495 mm radius 5
- Device dimensions (packed): 1040 x 740 x 505
- Net weight (kg): 30,8
- Gross weight (kg): 39,65

**Accessories**

**Special Accessories**

- 5Z9105X1 Charcoal filter
- 5Z9104X1 Air outlet kit right
- SLG5IX90 plinth ventilation grille

**Available Color Variations**

**Equipment features:**

Device type: Induction with integrated extractor fan  
 Type: Installation  
 Approval certificates: CE  
 Connection cable length (cm): 150  
 Diameter of the exhaust air spigot (mm): 150

**Consumption and connection values:**

Total connected load (W): 165  
 Protection: -  
 Voltage (V): 220/240  
 Frequency (Hz): 50/60  
 Plug type: Schuko  
 Approval certificates: CE

EAN-Nr.: 4251003105056

